

Rotating laser PR 2-HS



Applications

- Excavation
- Levelling formwork and pouring concrete
- Transferring and checking reference heights
- Setting out slopes

Advantages

- One button, one function makes the tool extremely easy to use
- Built to last newly designed shock-absorbing handles and receiver holder as well as the rugged IP 66 protected housing provide the most reliable performance in the toughest jobsite environment (MIL-STD-810G)
- Unaffected by sun and other light sources thanks to PulsePower technology
- Digital measurement indicates to the user precisely how much the measurement deviates from the target value
- Single manual slope mode at up to 45° using the PRA 79 slope adapter
- Lithium-ion battery featuring CPC technology for unique power management, can be charged while operating or in vehicles using the PUA 82 motor vehicle power adapter







PULSE**IIIPOWER**



Technical data			
Accuracy	±0.5 mm at 10 m		
Laser functionality	Manual slope, Horizontal levelling		
Self-levelling range at room temperature	±5 °		
Operating range with laser receiver (diameter)	2 - 600 m		
Laser class	<4.85 mW, 620-690 nm, Class 2 (IEC 60825-1:2007), Class II (FDA CFR 21 art. 1040)		
IP protection class	IP 66 (IEC 529)		
Battery type	Li-ion		
Weight with batteries	2.5 kg		
Dimensions (LxWxH)	200 x 200 x 230 mm		
Drop test height receiver	2 m		





Ordering designation	Package contents	Sales pack quantity	Item number
	1x Rotating laser PR 2-HS , 1x Battery pack PRA 84 assy, 1x Battery AA (2) alkaline, 1x Mains adapter PUA 81, 1x Laser receiver PRA 20 , 1x Laser receiver holder PRA 83 , 1x Case	1 pc	2071035

Please visit our website for the latest item numbers and related products.