

Ferrodetector PS 30



Applications

- Locating reinforcement, copper or aluminium pipes in concrete
- Locating copper or aluminium pipes in brick walls

Advantages

- Minimizes damage to rebar, copper and aluminium pipes when drilling
- Avoiding hitting rebar increases drill bit lifetime
- Unmatched localization accuracy
- Clear indication of detection with the red / green LED
- Easy to use, with one-button operation
- Ruggedly built for jobsite use



PULSE POWER



Technical data

Operating temperature range	-15 - 50 °C
Localization accuracy¹⁾	±10 mm
IP protection class	IP 54 (IEC 529)
Weight with batteries	420 g
Dimensions (LxWxH)	230 x 100 x 45 mm
Automatic switch-off	Yes
Low battery indication	Yes
Operating time with alkaline battery	10 h
Battery type	4 x 1.5 V (AAA)
Max. detection depth for non-ferrous metal objects¹⁾	80 mm

¹⁾ Performance and accuracy can be significantly affected by site conditions. See operating instructions.



Ordering designation	Package contents	Sales pack quantity	Item number
PS 30	1x Ferrodetector PS 30 , 2x Battery AAA (2) alkaline, 1x Marker pen , 1x Hand strap, 1x Toolbag PSA 66	1 pc	407920 ¹⁾

¹⁾ This is a non-stock item. For detailed lead time information please contact your Hilti representative.

Please visit our website for the latest item numbers and related products.