

Rotary hammer TE 1



Applications

- Everyday hammer drilling in concrete, masonry and natural stone
- Reverse rotation is useful for removing stuck drill bits

Advantages

- Single-mode SDS rotary hammer (hammer drilling)
- Sturdy motor with high load rating for maximum reliability
- High comfort due to compact size, light weight and "TE-C Click" chuck
- Electronic switch for precise hole-starting
- Lock-on button for continuous use



Technical data

| | |
|--|---------------------|
| Working mode | Hammer drilling |
| Optimum drilling diameter in concrete | 4 - 12 mm |
| Drilling diameter range for hammer drill bits | 4 - 18 mm |
| Single impact energy | 1.5 J |
| Triaxial vibration value for hammer drilling into concrete (ah,HD)¹⁾ | 15 m/s ² |
| A-weighted emission sound pressure level²⁾ | 89 dB (A) |
| Active Vibration Reduction | No |
| Dust removal module | TE DRS-S (optional) |
| Rated input power | 650 W |
| Full hammering frequency | 4500 impacts/minute |

¹⁾ according to EN 60745-2-6

²⁾ according to EN 60745



| Ordering designation | Package contents | Sales pack quantity | Item number |
|----------------------|---|---------------------|-------------|
| TE 1 | 1x Rotary hammer TE 1 230V GB , 1x Case | 1 pc | 355437 |

Please visit our website for the latest item numbers and related products.