

Cordless rotary hammer TE 2-A22



Applications

- Construction: light-duty drilling in concrete and masonry
- Interior finishing: installing partition walls and suspended ceilings
- Metal fabricators: fastening metal items such as handrails, staircases, sun blinds, barriers, etc.
- Electricians: electrical installation work
- Telecom contractors: installing telecom equipment, cables and switchgear

Advantages

- Cordless freedom with the performance of a corded tool
- Compact size and light weight for superior handling
- LED working light provides better visibility in dark areas
- Best-in-class system durability backed by Hilti Lifetime Service covering the tool and accessories

Technical data

Rated voltage	21.6 V
Battery capacity	1.6 Ah
Single impact energy	1.5 J
Full hammering frequency	5040 impacts/minute
Weight according to EPTA Procedure 01/2003	2.7 kg
Dimensions (LxWxH)	322 x 94 x 238 mm
Hammer drill bits (optimum dia. range)	4 - 12 mm
Drilling diameter range for hammer drill bits	4 - 16 mm
Working mode	Hammer drilling, Drilling only
A-weighted emission sound pressure level¹⁾	92 dB (A)

¹⁾ according to EN 60745



reddot design award winner 2013



Ordering designation	Package contents	Sales pack quantity	Item number
TE2-A22 Tool Body with Inserts	1x Cordless rotary hammer TE 2-A22 assy, 1x Case, 1x Hammer drill bit TE-CX 8/17, 1x Hammer drill bit TE-CX 10/17, 1x Hammer drill bit TE-CX 12/17	1 pc	3520552

Please visit our website for the latest item numbers and related products.