

Diamond coring tool DD 160



Applications

- Rig-based wet drilling in concrete for pipe penetrations in plumbing, heating and air conditioning installations
- Stitch drilling for cable trays and ventillation ducts
- Drilling blind holes for large-diameter anchors, reinforcing bars and the installation of railings and barriers

Advantages

- Sturdy three-speed gearing for outstanding coring performance across the entire diameter range
- The power control LED helps new users to achieve the optimum rate of drilling progress and maximum core bit life
- Less downtime: the service indicator reminds users in good time when servicing is due
- Clear and concise range of accessories for added versatility
- BI+ quick-release chuck system for keyless exchange of core bits

HILT	1 Year
LIPETIME SERVICE TH	NO COSTS
Lifetime	Lifetime
REPAIR COST LIMIT	MANUFACTURER'S WARRANTY











Technical data	
Number of gears	3
Rotation speed	gear 1: 420 rpm; gear 2: 700 rpm; gear 3: 1570 rpm
Drilling range	Rig-based wet: 25-202 mm
Chuck type	BI+
Max. drilling depth	450 mm
Weight of complete system	16 kg
Dimensions (LxWxH)	450 x 195 x 315 mm



reddot design	award

Ordering designation	Base plate dimensions (LxW)	Package contents	Sales pack quantity	Item number
DD160 (110V) with Clamping Nut & Spindle	225 x 164 mm	1x Diamond coring tool DD 160 110V , 1x Chuck BI+ assy, 1x Jack screw DD-CS M16 S , 1x Drilling stand DD-ST 160 SFL	1 pc	35085871)
DD160 (230V) with Clamping Nut & Spindle		1x Diamond coring tool DD 160 230V , 1x Chuck BI+ assy, 1x Jack screw DD-CS M16 S , 1x Drilling stand DD-ST 160 SFL	1 pc	3508206

¹⁾ This is a non-stock item. For detailed lead time information please contact your Hilti representative.

Please visit our website for the latest item numbers and related products.