

**Firestop foam CP 620**



**Applications**

- Concrete, drywall and masonry
- Multiple and mixed penetrations
- Single cables, cable bundles and cable trays
- Metal pipes
- Suitable for irregular and difficult-to-reach openings

**Advantages**

- Innovative firestopping solution for complex and difficult-to-reach applications
- Virtually impervious to smoke
- Excellent water and vapour resistance
- Single-sided installation possible
- Easy to use in openings where access is poor



**Technical data**

<b>Foam yield (up to)</b>	1.9 l
<b>Intumescent</b>	Yes
<b>Acoustics performance</b>	Test report available
<b>Tested in accordance with</b>	UL 1479, CAN/ULC-S102
<b>Approx. tack-free time (at 23°C / 50% rel. humidity)</b>	35 s
<b>Approx. cut time (at 23°C / 50% rel. humidity)</b>	2 min
<b>Fire rating</b>	See Approvals
<b>LEED VOC</b>	1.3 g/l
<b>Storage and transportation temperature range</b>	5 - 25 °C
<b>Temperature resistance range</b>	-30 - 100 °C



Firestop Systems and Construction Chemicals

Ordering designation	Package contents	Sales pack quantity	Item number
CP 620	1x Firestop foam CP 620 EN/DE/FR/IT/NL/TH	1 pc	2025083

Please visit our website for the latest item numbers and related products.